

# Material Safety Data Sheet

## 24 Hour Emergency Phone Numbers:

Medical: 1-800-327-3874  
1-513-558-5111

Transportation:  
1-800-535-5053  
1-352-323-3500

.....  
 \*NOTE: National Response Center emergency numbers to be used  
 \*only in the event of chemical emergencies involving a spill, leak,  
 \*fire, exposure or accident involving chemicals.  
 .....

**IMPORTANT:** Provide this information to employees, customers, and users of this product. Read this MSDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this MSDS are further described in Section 16.

## Section 1 - Chemical Product / Company Information

This Material Safety Data Sheet is available in Canadian French and Hispanic American Spanish upon request.  
 Esta hoja de datos de la seguridad de los materiales está disponible en francés canadiense y en español a su solicitud.  
 Los Datos de Seguridad del Producto pueden obtenerse en Espanol si lo requiere.

**Product Name:** Floor Tile Adhesive  
**Product UPC Number:** 7079800136, 7079800137, 7079800139, 7079872044, 7079872042, 7079872040  
**Product Use/Class:** Latex Floor Covering Adhesive  
**Manufacturer:** DAP Inc.  
 2400 Boston Street Suite 200  
 Baltimore, MD 21224-4723  
 888-327-8477 (non-emergency matters)

**Revision Date:** 03/24/2004  
**Supercedes:** 03/04/1999  
**MSDS Number:** 00077272001

## Section 2 - Composition / Information On Ingredients

Chemical Name	CASRN	WT%	ACGIH TWA	ACGIH STEL	ACGIH CEIL	OSHA TWA	OSHA STEL	OSHA CEIL	Skin
Petroleum hydrocarbon oil	64742-52-5	10-30	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.	No
Kaolin	1332-58-7	3-7	2 MGM3	N.E.	N.E.	N.E.	N.E.	N.E.	No
Urea	57-13-6	1-5	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.	No
Ethylene glycol	107-21-1	1-5	N.E.	N.E.	100 MGM3	N.E.	N.E.	N.E.	No
Silica, crystalline	14808-60-7	<0.06	0.05 MGM3	N.E.	N.E.	(10-%SiO <sub>2</sub> )/2 mg/m <sup>3</sup>	N.E.	N.E.	No

### Exposure Notes:

**Important:** Listed Permissible Exposure Levels (PEL) are from the U.S. Dept. of Labor OSHA Final Rule Limits (CFR 29 1910.1000); these limits may vary between states.

**Note:** An employee's skin exposure to substances having a "YES" in the "SKIN" column in the table above shall be prevented or reduced to the extent necessary under the circumstances through the use of gloves, coveralls, goggles or other appropriate personal protective equipment, engineering controls or work practices

## Section 3 - Hazards Identification

**Emergency Overview:** A Tan Liquid product. WARNING! Causes eye, skin, nose, throat, lung and respiratory tract irritation. Harmful or fatal if swallowed. This product contains ethylene glycol.

Refer to other MSDS sections for other detailed information.

**Effects Of Overexposure - Eye Contact:** May cause eye irritation.

**Effects Of Overexposure - Skin Contact:** May cause skin irritation. Prolonged or repeated contact with skin may cause irritation.

**Effects Of Overexposure - Inhalation:** Vapors may be irritating to eyes, nose, throat, and lungs.

**Effects Of Overexposure - Ingestion:** Harmful or fatal if swallowed. Ingestion of ethylene glycol can cause gastrointestinal irritation, nausea, vomiting, diarrhea and if ingested in sufficient quantities, death. If ingested, may cause vomiting, diarrhea, and depressed respiration. Aspiration of material into the lungs due to vomiting can cause chemical pneumonitis, which can be fatal.

**Effects Of Overexposure - Chronic Hazards:** Overexposure may cause kidney, cardiovascular, skin and liver damage. Prolonged or repeated contact with skin results in irritation and dermatitis. Studies have shown that repeated inhalation of ethylene glycol has produced adverse cardiovascular changes in laboratory animals. Ethylene Glycol may cause kidney and liver damage upon prolonged and repeated overexposures. Ethylene glycol has been shown to cause birth defects in laboratory animals.

**Primary Route(s) Of Entry:** Skin Contact, Skin Absorption, Inhalation

**Medical Conditions which May be Aggravated by Exposure:** None known.

## Section 4 - First Aid Measures

**First Aid - Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

**First Aid - Skin Contact:** Wash off with soap and water.

**First Aid - Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

**First Aid - Ingestion:** If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

**Note to Physician:** No Information.

**COMMENTS:** Call Medical Emergency at 1-800-327-3874 if any irritation or complication arise from any of the above routes of entry.

## Section 5 - Fire Fighting Measures

**Flash Point, F:** >212

**Method:** (Seta Closed Cup)

**Lower Explosive Limit, %:** Not Established

**Upper Explosive Limit, %:** Not Established

**Extinguishing Media:** Carbon Dioxide, Dry Chemical, Foam, Water Fog

**Unusual Fire And Explosion Hazards:** None known.

**Special Firefighting Procedures:** Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

## Section 6 - Accidental Release Measures

**Steps To Be Taken If Material Is Released Or Spilled:** Wear proper protective equipment as specified in Section 8. Wet dried material before scraping up and place into containers.

## Section 7 - Handling And Storage

**Handling:** KEEP OUT OF REACH OF CHILDREN! Provide fresh air such that chemical odors cannot be detected during use and while drying. Avoid breathing vapors. Use in well ventilated area. Do not sand, dry sweep, dry scrape, drill, saw, beadblast, mechanically chip, pulverize or otherwise machine existing resilient flooring, backing, lining felt, or asphaltic "cut-back" adhesives. These products may contain either asbestos fibers or crystalline silica. Avoid creating dust. Inhalation of such dust is a cancer and respiratory tract hazard. See current edition of the Resilient Floor Covering Institute's publication, "Recommended Work Practices for Removal of Resilient Floor Coverings", for detailed information and instructions addressed to the task of removing all resilient floor covering materials. Avoid contact with eyes, skin and clothing. Construction and repair activities can adversely affect indoor air quality. Consult with occupants or a representative (i.e. maintenance, building manager, industrial hygienist, or safety officer) to determine ways to minimize impact. Wash thoroughly after handling.

**Storage:** Store containers away from excessive heat and freezing. Keep containers tightly closed. Store away from caustics and oxidizers.

## Section 8 - Exposure Controls / Personal Protection

**Precautionary Measures:** Please refer to other sections and subsections of this MSDS.

**Engineering Controls:** Use only in well-ventilated areas. Provide sufficient general and/or local exhaust ventilation to maintain exposure below recommended exposure limit.

**Respiratory Protection:** A respiratory protection program that meets the OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. Respirator use is not expected to be necessary under normal conditions of handling. In emergency situations, use of a NIOSH-approved respirator may be required.

**Skin Protection:** Wear rubber gloves.

**Eye Protection:** Goggles or safety glasses with side shields.

**Other protective equipment:** None.

**Hygienic Practices:** Remove and wash contaminated clothing before re-use. Although this product is not considered an eye irritant, inhalation hazard, or a skin contact hazard under normal conditions, it is advisable that personnel minimize skin contact, inhalation of vapors, and eye contact.

## Section 9 - Physical And Chemical Properties

<b>Boiling Range:</b>	Not Established	<b>Vapor Density:</b>	Heavier Than Air
<b>Odor:</b>	Very Slight Ammonia	<b>Odor Threshold:</b>	Not Established
<b>Appearance:</b>	No Data Available	<b>Evaporation Rate:</b>	Slower Than n-Butyl Acetate
<b>Solubility in H2O:</b>	Not Established	<b>Specific Gravity:</b>	1.042
<b>Freeze Point:</b>	Not Established	<b>pH:</b>	Between 7.0 and 12.0
<b>Vapor Pressure:</b>	Not Established	<b>Viscosity:</b>	Not Established
<b>Physical State:</b>	Paste		

When reported, vapor pressure of this product has been calculated theoretically based on its constituent makeup and has not been determined experimentally.

(See section 16 for abbreviation legend)

## Section 10 - Stability And Reactivity

**Conditions To Avoid:** Excessive heat and freezing.

**Incompatibility:** Strong oxidizing agents. Strong bases.

**Hazardous Decomposition Products:** Normal decomposition products, i.e., COx, NOx.

**Hazardous Polymerization:** Hazardous polymerization will not occur under normal conditions.

**Stability:** Stable under normal conditions.

## Section 11 - Toxicological Information

**Product LD50:** Not Established

**Product LC50:** Not Established

CASRN	Chemical Name	LD50	LC50	wt:wt%
57-13-6	Urea	Rat:8471 mg/kg	-----	1 - 5
107-21-1	Ethylene glycol	Rat:4700 mg/kg	Rat:10876 mg/kg	1 - 5
100-40-3	4-Vinylcyclohexene	16620 mg/kg	4000 ppm rat	<0.002
106-99-0	1,3-Butadiene	-----	Rat:285 gm/m3/4H	<0.0003

**Carcinogenicity:**

CAS No.	Chemical Name	ACGIH	OSHA	IARC	NTP	wt:wt%
14808-60-7	Silica, crystalline	Suspected human carcinogen.	-----	Human carcinogen.	Known carcinogen.	<0.06
100-40-3	4-Vinylcyclohexene	Confirmed animal carcinogen with unknown relevance to humans.	-----	Possible carcinogen.	-----	<0.002
106-99-0	1,3-Butadiene	Suspected human carcinogen.	Cancer hazard.	Probable carcinogen.	Known carcinogen.	<0.0003
140-88-5	Ethyl acrylate	-----	-----	Possible carcinogen.	-----	<0.00008
50-00-0	Formaldehyde	Suspected human carcinogen.	Potential cancer hazard.	Probable carcinogen.	Anticipated carcinogen.	<0.00003

**Significant Data with Possible Relevance to Humans:** None

## Section 12 - Ecological Information

**Ecological Information:** Ecological injuries are not known or expected under normal use.

## Section 13 - Disposal Information

**Disposal Information:** Dispose of material in accordance with all federal, state and local regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

**EPA Waste Code if Discarded (40 CFR Section 261):** None

## Section 14 - Transportation Information

**DOT Proper Shipping Name:** None

**Packing Group:** N.A.

**DOT Technical Name:** None  
**DOT Hazard Class:** N.A.

**Hazard Subclass:** N.A.  
**DOT UN/NA Number:** None

## Section 15 - Regulatory Information

### CERCLA - SARA Hazard Category:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Immediate Health Hazard, Chronic Health Hazard

### SARA Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name	CAS Number
Ethylene glycol	107-21-1

### Toxic Substances Control Act:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

Chemical Name	CAS Number	WT%
5-Chloro-2-methyl-4-isothiazoli	26172-55-4	<0.002
2-Methyl-4-isothiazolin -3-one	2682-20-4	<0.0007

### U.S. State Regulations:

#### New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product:

None

#### Pennsylvania Right-to-Know:

The following non-hazardous ingredients are present in the product at greater than 3%:

None

#### California Proposition 65:

Warning: The following ingredients present in the product are known to the State of California to cause cancer:

Chemical Name	CAS Number	Definition	Date Listed	wt:wt%
Silica, crystalline	14808-60-7	Carcinogenic.	Listed: October 1, 1988	<0.06
			Listed: May 1,	

4-Vinylcyclohexene	100-40-3	Carcinogenic.	1996	<0.002
1,3-Butadiene	106-99-0	Carcinogenic.	Listed: April 1, 1988	<0.0003
Ethyl acrylate	140-88-5	Carcinogenic.	Listed: July 1, 1989	<0.00008
Formaldehyde	50-00-0	Carcinogenic.	Listed: January 1, 1988	<0.00003

Warning: The following ingredients present in the product are known to the State of California to cause birth defects or other reproductive harm.

None

## Section 16 - Other Information

### HMIS Ratings:

Health:                      Flammability: 1                      Reactivity: 0                      Personal Protection: 0

**VOLATILE ORGANIC COMPOUNDS, GR/LTR: 26.8    LB/GAL: 0.2    WT%: 1.643**

### REASON FOR REVISION:

<b>Legend:</b>	N.A. – Not Applicable	ACGIH – American Conference of Governmental Industrial Hygienists
	N.E. – Not Established	SARA – Superfund Amendments and Reauthorization Act of 1986
	N.D. – Not Determined	NJRTK – New Jersey Right-to-Know Law
	VOC – Volatile Organic Compound	OSHA – Occupational Safety and Health Administration
	PEL – Permissible Exposure Limit	HMIS – Hazardous Materials Identification System
	TLV – Threshold Limit Value	NTP – National Toxicology Program
	STEL – Short Term Exposure Limit	CEIL – Ceiling Exposure Limit
	LD50 – Lethal Dose 50	LC50 – Lethal Concentration 50
	F – Degree Fahrenheit	C – Degree Celcius
	MSDS – Material Safety Data Sheet	CASRN – The Chemical Abstracts Service Registry Number

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. **NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS.** Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.

<End of MSDS>