SAFETY DATA SHEET

1. Identification

Product identifier Lectra-Motive® Electric Parts Cleaner

Other means of identification

05018 Product code

Recommended use Energized electrical cleaner

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

CRC Industries, Inc. Company name

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

General Information 215-674-4300 **Technical** 800-521-3168

Assistance

800-272-4620 **Customer Service** 24-Hour Emergency 800-424-9300 (US)

(CHEMTREC) 703-527-3887 (International) Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Gases under pressure Compressed gas Acute toxicity, inhalation Category 4 Health hazards

Skin corrosion/irritation Category 2 Carcinogenicity Category 1B

Specific target organ toxicity, single exposure Category 3 narcotic effects Category 2

Environmental hazards Hazardous to the aquatic environment,

long-term hazard

Not classified. **OSHA** defined hazards

Label elements



Signal word Danger

Contains gas under pressure; may explode if heated. Causes skin irritation. May cause **Hazard statement** drowsiness or dizziness. May cause cancer. Toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 49°C/120°F. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Avoid breathing gas. Wash thoroughly after handling. Wear protective gloves/protective

clothing/eye protection/face protection. Avoid release to the environment.

Response If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep

comfortable for breathing. Call a poison center/doctor if you feel unwell. If exposed or concerned:

Get medical attention. Collect spillage.

Material name: Lectra-Motive® Electric Parts Cleaner

SDS US 1/9 05018 Version #: 03 Revision date: 01-20-2016 Issue date: 12-20-2013

Storage Store locked up. Protect from sunlight. Store in a well-ventilated place. Exposure to high

temperature may cause can to burst.

Disposal

Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen chloride and possibly phosquene.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%	
Tetrachloroethylene	Perchloroethylene	127-18-4	90 - 100	
Carbon dioxide		124-38-9	1 - 5	

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

InhalationRemove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contactRemove contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

Most important symptoms/effects, acute and delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of eyes and mucous membranes. Irritation of nose and throat. Skin irritation. May cause redness and pain.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

General information

Dry chemical, CO2, or water spray.

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Exposure to high temperature may cause can to burst. When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen chloride and possibly phosgene.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-fighting equipment/instructions

In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop the flow of material, if this is without risk. Collect spillage. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

SDS US

Environmental precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist or vapor. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Avoid release to the environment. Do not empty into drains. For product usage instructions, please see the product label.

Conditions for safe storage, including any incompatibilities

Oc

Level 1 Aerosol.

Contents under pressure. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 49 °C/120 °F. Do not handle or store near an open flame, heat or other sources of ignition. Exposure to high temperature may cause can to burst. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Components	Туре	Value	
Carbon dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
,		5000 ppm	
US. OSHA Table Z-2 (29 CFR 1910	.1000)		
Components	Туре	Value	
Tetrachloroethylene (CAS 127-18-4)	Ceiling	200 ppm	
•	TWA	100 ppm	
US. ACGIH Threshold Limit Value	s		
Components	Туре	Value	
Carbon dioxide (CAS 124-38-9)	STEL	30000 ppm	
,	TWA	5000 ppm	
Tetrachloroethylene (CAS 127-18-4)	STEL	100 ppm	
·	TWA	25 ppm	
US. NIOSH: Pocket Guide to Cher	nical Hazards		
Components	Туре	Value	
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
•		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	

Bio

ACGIH Biological Exposu Components	ıre Indices Value	Determinant	Specimen	Sampling Time
Tetrachloroethylene (CAS 127-18-4)	0.5 mg/l	Tetrachloroethy lene	Blood	*
	3 ppm	Tetrachloroethy lene	End-exhaled air	*
* - For sampling details, please see the source document.				

Material name: Lectra-Motive® Electric Parts Cleaner

Exposure guidelines

US - Minnesota Haz Subs: Skin designation applies

Tetrachloroethylene (CAS 127-18-4)

Skin designation applies.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower should be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Viton®. Polyvinyl alcohol (PVA). Nitrile. Silver Shield®

Other Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Aerosol.
Color Colorless.
Odor Irritating.
Odor threshold 50 ppm

pH Not available.

Melting point/freezing point
Initial boiling point and boiling

range

-8.1 °F (-22.3 °C) estimated 250.3 °F (121.3 °C) estimated

Flash point None (Tag Closed Cup)

Evaporation rateVery fast.Flammability (solid, gas)Not available.Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Vapor pressure 1352.4 hPa estimated

Vapor density 5.76 (air = 1)

Relative density 1.62

Solubility (water) 0.02 % (77 °F (25 °C))

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature

Decomposition temperature

Viscosity (kinematic)

Percent volatile

Not available.

Not available.

97.7 % estimated

Other information

Partition coefficient

2.88

(oil/water)

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Heat, flames and sparks. Contact with incompatible materials. Conditions to avoid

When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal

corrosive gases such as hydrogen chloride and possibly phosgene.

Strong oxidizing agents. Strong acids. Strong bases. Incompatible materials

Hazardous decomposition

products

Hydrogen chloride. Trace amounts of chlorine and phosgene. Carbon oxides. Halogenated

materials. Carbonyl halides.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful. May cause drowsiness and dizziness. Headache. Nausea,

vomiting.

Skin contact Causes skin irritation.

Direct contact with eyes may cause temporary irritation. Eye contact

Ingestion Ingestion of large amounts may produce gastrointestinal disturbances including irritation, nausea,

and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat.

Irritation of eyes and mucous membranes. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Narcotic effects

Product Species Test Results

Lectra-Motive® Electric Parts Cleaner

Acute

Dermal

LD50 Rabbit 3305 mg/kg estimated

Inhalation

LC50 Rat 20 mg/l, 4 Hours estimated

Oral

LD50 Rat 2692 mg/kg estimated

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

May cause cancer. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

05018 Version #: 03 Revision date: 01-20-2016 Issue date: 12-20-2013

Tetrachloroethylene (CAS 127-18-4) 2A Probably carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Tetrachloroethylene (CAS 127-18-4) Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Based on available data, the classification criteria are not met.

Material name: Lectra-Motive® Electric Parts Cleaner

^{*} Estimates for product may be based on additional component data not shown.

12. Ecological information

cotoxicity	Toxic to a	Toxic to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.		
Product		Species	Test Results	
Lectra-Motive® Electr	ric Parts Cleaner			
Aquatic				
Fish	LC50	Fish	19.1805 mg/l, 96 hours estimated	
Components		Species	Test Results	
Tetrachloroethylene (CAS 127-18-4)			
Aquatic				
Fish	LC50	Rainbow trout, donaldson trout	4.73 - 5.27 mg/l, 96 hours	

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability Not available.

Bioaccumulative potential Not available.

Partition coefficient n-octanol / water (log Kow)

Tetrachloroethylene 2.88

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

(Oncorhynchus mykiss)

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products

This material and its container must be disposed of as hazardous waste. Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical

or used container. Dispose in accordance with all applicable regulations.

Hazardous waste code D039: Waste Tetrachloroethylene

F001: Waste Halogenated Solvent - Spent Halogenated Solvent Used in Degreasing

F002: Waste Halogenated Solvent - Spent Halogenated Solvent

US RCRA Hazardous Waste U List: Reference

Tetrachloroethylene (CAS 127-18-4) U210

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, poison, Limited Quantity

Transport hazard class(es)

Class 2.2
Subsidiary risk 6.1(PGIII)
Label(s) 2.2, 6.1
Packing group Not applicable.

Special precautions for user Forbidden from transportation by air.

Packaging exceptions 306
Packaging non bulk None
Packaging bulk None

IATA

UN number UN1950

UN proper shipping name Aerosols, non-flammable, containing substances in Division 6.1, Packing Group III **Transport hazard class(es)**

Class 2.2 Subsidiary risk 6.1

Packing group Not applicable.

Environmental hazards No.

Material name: Lectra-Motive® Electric Parts Cleaner

ERG Code 2P

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1950 **UN proper shipping name** AEROSOLS

Transport hazard class(es)

Class 2 Subsidiary risk 6.1

Packing group Not applicable.

Environmental hazards No.

EmS Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Tetrachloroethylene (CAS 127-18-4)

CERCLA Hazardous Substance List (40 CFR 302.4)

Tetrachloroethylene (CAS 127-18-4)

CERCLA Hazardous Substances: Reportable quantity

Tetrachloroethylene (CAS 127-18-4) 100 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Tetrachloroethylene (CAS 127-18-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug

Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Immediate Hazard - Yes
Hazard categories Delayed Hazard - Yes

Fire Hazard - No Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely No hazardous substance

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Tetrachloroethylene (CAS 127-18-4)

US. New Jersey Worker and Community Right-to-Know Act

Carbon dioxide (CAS 124-38-9)

US. Massachusetts RTK - Substance List

Carbon dioxide (CAS 124-38-9) Tetrachloroethylene (CAS 127-18-4)

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Rhode Island RTK

Tetrachloroethylene (CAS 127-18-4)

US. New Jersey Worker and Community Right-to-Know Act

Tetrachloroethylene (CAS 127-18-4)

US. Pennsylvania Worker and Community Right-to-Know Law

Tetrachloroethylene (CAS 127-18-4) Carbon dioxide (CAS 124-38-9)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Tetrachloroethylene (CAS 127-18-4) Listed: April 1, 1988

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR

0 %

51.100(s))

Consumer products (40 CFR 59, Subpt. C) Not regulated

State

Consumer products

This product is regulated as an Energized Electrical Cleaner for the following states: California, Connecticut, Delaware, District of Columbia, Illinois, Indiana, Maine, Maryland, Massachusetts, Michigan, New Jersey, New York, Ohio, Pennsylvania, Rhode Island and Virginia. It is for energized equipment use only. It is not to be used for motorized vehicle maintenance or their parts. This product is compliant for use in all 50 states.

0 % VOC content (CA) 0 % VOC content (OTC)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

16. Other information, including date of preparation or last revision

Issue date 12-20-2013 01-20-2016 **Revision date** Prepared by Allison Cho Version # 03

Further information CRC # 491G

Material name: Lectra-Motive® Electric Parts Cleaner

HMIS® ratings Health: 2*

Flammability: 0 Physical hazard: 0 Personal protection: B

NFPA ratings

Health: 2 Flammability: 0 Instability: 0

NFPA ratings



Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.