

Permatex, Inc.  
 10 Columbus Blvd.  
 Hartford, CT 06106 USA  
 Telephone: 1-87-Permatex  
 (877) 376-2839  
 Emergency: 800-255-3924  
 International Emergency: +01-813-248-0585

## Material Safety Data Sheet

### 1. PRODUCT IDENTIFICATION

**Product Name:** 133K ANTI-SEIZE LUBRICANT 8OZ  
**Item No:** 80078  
**Product Type:** Lubricant

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC 64742-52-5	20-40	Not listed	Not listed
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC 64742-53-6	20-40	5 mg/m <sup>3</sup> TWA ACGIH	Not listed
CALCIUM OXIDE 1305-78-8	15-25	2 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>
ALUMINIUM POWDER 7429-90-5	<10	1 mg/m <sup>3</sup>	15 mg/m <sup>3</sup>
GRAPHITE 7782-42-5	<10	2 mg/m <sup>3</sup>	15 mppcf
MINERAL OIL 64741-44-2	<5	5 mg/m <sup>3</sup>	Not listed

### 3. HAZARDS IDENTIFICATION

**Toxicity:** May cause eye and skin irritation. May cause nose, throat and respiratory irritation. May cause gastrointestinal irritation. High concentrations may cause central nervous system (CNS) depression.

**Primary Routes of Entry:** Eye and skin contact, ingestion, inhalation

**Signs and Symptoms of Exposure:** Overexposure may cause eye and skin redness, difficulty breathing and vomiting. Excessive accidental exposure may cause headache, dizziness, nausea and mild respiratory irritation. Inhalation of dust at levels above recommended exposure limit may cause metallic or sweet taste, irritation of pharynx and possible ulceration with perforation of the nasal septum.

**Medical Conditions Recognized as Being Aggravated by Exposure:** Persons with respiratory problems such as emphysema and asthma should avoid inhalation. Since this product contain copper compounds, individuals with Wilson's Disease should avoid exposure to this product.

### 4. FIRST AID MEASURES

**Ingestion:** Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

**Inhalation:** Move to fresh air in case of accidental inhalation of vapours. If symptoms persist, call a physician.

**Skin Contact:** Wash off with soap and water. If skin irritation persists, call a physician.

**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

### 5. FIRE FIGHTING MEASURES

**Flash Point °F(C°):** >200° F TCC

**Recommended Extinguishing Media:** Carbon Dioxide, Dry Chemicals, Foam.

**Special Fire-Fighting Procedures:** Firefighters should wear self-contained breathing apparatus. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

**Hazardous Products of Combustion:** Oxides of carbon, Metal oxide fumes

**Unusual Fire/Explosion Hazards:** May ignite when sufficient heat is applied.

### 5. FIRE FIGHTING MEASURES

**Lower Explosive Limit:** 30% aluminum metal; 1% oil  
**Upper Explosive Limit:** 7% oil

### 6. ACCIDENTAL RELEASE MEASURES

**Spill Procedures:** Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

### 7. HANDLING AND STORAGE

**Storage:** Store away from heat, sparks or open flame. Do not store at temperatures above 100°F (38°C).  
**Handling:** Avoid prolonged skin contact. Keep away from eyes. Do not inhale vapors. Do not use near heat, sparks or open flame. Wash hands and face after handling this compound.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Eyes:** Safety glasses.  
**Skin:** Neoprene or nitrile gloves recommended.  
**Ventilation:** General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.  
**Respiratory Protection:** An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Silver paste  
**Odor:** Petroleum distillates  
**Boiling Point:** Not determined  
**pH:** Does not apply  
**Solubility in Water:** Nil  
**Specific Gravity:** 1.17  
**VOC(Wt.%):** None  
**Vapor Pressure:** <5 mm Hg  
**Vapor Density (Air=1):** <1  
**Evaporation Rate:** <1 (butyl acetate = 1)

### 10. STABILITY AND REACTIVITY

**Chemical Stability:** Stable at normal conditions  
**Hazardous Polymerization:** Will not occur.  
**Incompatibilities:** Strong oxidizers, alkalis, mineral acids, selected amines.  
**Conditions to Avoid:** Heat.  
**Hazardous Products of Combustion:** Oxides of carbon, Metal oxide fumes

### 11. TOXICOLOGICAL INFORMATION

See Section 3

### 12. ECOLOGICAL INFORMATION

No data available

### 13. DISPOSAL CONSIDERATIONS

**Recommended Method of Disposal:** Disposal should be made in accordance with federal, state and local regulations..  
**US EPA Waste Number:** NH - Not a RCRA Hazardous Waste Material

### 14. TRANSPORTATION INFORMATION

**DOT (49CFR 172)**

**Ground Transport (DOT)**

**DOT Shipping Name:** Not Regulated  
**Hazard Class:** None  
**UN/ID Number:** None

**IATA**

**Proper Shipping Name:** Not regulated  
**Class or Division:** None

## 14. TRANSPORTATION INFORMATION

**UN/ID Number:** None

### IMDG

**Proper Shipping:** Not regulated

**Hazard Class:** None

**UN Number:** None

**Marine Pollutant:** None

## 15. REGULATORY INFORMATION

**SARA 313 Chemicals:** The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

**California Proposition 65:** No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level

**TSCA Inventory Status:** All components of this product are listed (or exempt) on the EPA TSCA inventory.

## 16. OTHER INFORMATION

**Estimated NFPA Rating:** HEALTH 1, FLAMMABILITY 1 REACTIVITY 1 .

**Estimated HMIS Classification:** HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

**Prepared By:** Denise Boyd, Manager-Environmental, Health & Safety  
**Company:** Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

**Revision Date:** April 28, 2009

**Revision** 2

**Number:**

**Telephone No.:** 1-87-Permatex (877) 376-2839