

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

844 **Product number**

Product name Water Base Stainless Steel Maintainer

Effective date 22-Jul-2008

Company information Claire Manufacturing

500 Vista Ave.

Addison, IL 60101 United States General Assistance 630-543-7600

Company phone 800-424-9300 **Emergency telephone US**

Emergency telephone outside US 703-527-3887

Version # 08

Supersedes date 18-Jul-2008

2. Hazards Identification

CONTENTS UNDER PRESSURE. Aerosol. Pressurized container may explode when **Emergency overview**

exposed to heat or flame.

Irritating to eyes. Prolonged exposure may cause chronic effects.

Potential health effects

Routes of exposure Ingestion. Skin contact. **Eyes** Causes eye irritation.

Skin Prolonged or repeated contact can result in defatting and drying of the skin which may

result in skin irritation and dermatitis (rash).

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage.

Components of the product may be absorbed into the body by ingestion.

Target organs Central nervous system. Lungs.

Chronic effects May cause central nervous system disorder (e.g., narcosis involving a loss of

coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage.

May cause delayed lung damage.

3. Composition / Information on Ingredients

Components	CAS#	Percent
Synthetic Isoparaffinic Hydrocarbon	64742-47-8	15 - 20
n-Butane	106-97-8	10 - 15
Odorless Mineral Spirits	64742-48-9	8 - 10
Propane	74-98-6	5 - 8
Non-hazardous and other components below reportable levels		40 - 60

4. First Aid Measures

First aid procedures

Eve contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation

develops or persists.

Skin contact Immediately take off all contaminated clothing. Wash off with warm water and soap. Get

medical attention if irritation develops or persists.

Inhalation Move to fresh air. If symptoms persist, get medical attention.

Ingestion If material is ingested, immediately contact a poison control center. Rinse mouth. Do not

induce vomiting without advice from poison control center. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask

equipped with a one-way valve or other proper respiratory medical device.

trade_name Water Base Stainless Steel Maintainer MSDS US

5. Fire Fighting Measures

Flammable properties

Containers may explode when heated. Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.

Extinguishing media

Suitable extinguishing media

Protection of firefighters

Specific hazards arising from

the chemical

Protective equipment and precautions for firefighters Foam. Dry chemical. Carbon dioxide (CO2). Do not use water jet.

Fire may produce irritating, corrosive and/or toxic gases.

In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

6. Accidental Release Measures

Methods for containment

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk. Prevent entry into waterways, sewers, basements or confined areas.

Methods for cleaning up

Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

7. Handling and Storage

Handling

Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not get this material in contact with eyes. Do not get this material in contact with skin. Wear personal protective equipment. Avoid prolonged exposure.

Storage

Level 2 Aerosol.

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat, sparks, and flame. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Do not store, incinerate, or heat this material above 120 degrees Fahrenheit.

8. Exposure Controls / Personal Protection

Exposure limits

_	_	_	_	_	_
Α	r	c	ı	L	_
~	·	u	ı	Г	1

Components	CAS#	TWA	STEL	Ceiling
n-Butane	106-97-8	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
OSHA				
Components	CAS#	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established

Personal protective equipment

Eye / face protection

Wear chemical goggles.

Skin protection

trade_name

Wear appropriate chemical resistant clothing. Protective gloves.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Appearance Compressed liquefied gas. **Boiling point** 197.6 °F (92.2 °C) estimated

Water Base Stainless Steel Maintainer

Color White.

Flammability (HOC) 20.9239 kJ/g estimated

Flash back No.

Flash point -156 °F (-104.4 °C)

Form Aerosol.

Odor Characteristic.
pH 6.5 - 7.5

Physical state Liquid.

Pressure 35 - 45 psig @ 70F

Solubility Negligible Specific gravity 0.807

10. Chemical Stability & Reactivity Information

Chemical stability Risk of ignition.

Conditions to avoid Heat, flames and sparks.

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological Information

Acute effectsAcute LD50: 8963 mg/kg estimated, Rat, DermalSensitizationNot expected to be hazardous by OSHA criteria.Reproductive effectsNot expected to be hazardous by OSHA criteria.TeratogenicityNot expected to be hazardous by OSHA criteria.

12. Ecological Information

Ecotoxicity Components of this product have been identified as having potential environmental

concerns.

LC50 267 mg/L estimated, Fish, 96.00 Hours,

13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 F

Disposal instructionsContents under pressure. Dispose of this material and its container at hazardous or special waste collection point. Do not incinerate sealed containers. Do not allow this

special waste collection point. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name Consumer commodity

Hazard class ORM-D Subsidiary hazard class None

Additional information:

Packaging exceptions 156, 306
Packaging non bulk 156, 306
Packaging bulk None

Product #: 844 Revision date: 22-JUL-2008 Print date: 22-JUL-2008

IMDG

Basic shipping requirements:

Proper shipping name AEROSOLS, flammable

Hazard class 2.1 **UN** number 1950

Additional information:

Packaging exceptions LTD QTY

Item 5F Labels required None **Transport Category** 2

IATA

Basic shipping requirements:

Proper shipping name Aerosols, flammable

Hazard class 2.1 **UN** number 1950

Additional information:

Packaging exceptions LTD QTY Labels required 2.1





15. Regulatory Information

US federal regulations OSHA Process Safety Standard: This material is not known to be hazardous by the

OSHA Highly Hazardous Process Safety Standard, 29 CFR 1910.119.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

CERCLA/SARA Hazardous Substances - Not applicable.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous

chemical

Yes

CERCLA (Superfund) reportable quantity

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

Section 302 extremely hazardous substance

Section 311 hazardous chemical Yes

Inventory status

Country(s) or region Inventory name On inventory (yes/no)* China Inventory of Existing Chemical Substances in China (IECSC) Yes Europe European Inventory of New and Existing Chemicals (EINECS) No European List of Notified Chemical Substances (ELINCS) Europe No Japan Inventory of Existing and New Chemical Substances (ENCS) No Korea Existing Chemicals List (ECL) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations

U.S. - Pennsylvania - RTK (Right to Know) List

106-97-8 n-Butane Present 74-98-6 Present Propane

16. Other Information

Further information HMIS® is a registered trade and service mark of the NPCA.

MSDS US 4/5 Revision date: 22-JUL-2008 Print date: 22-JUL-2008 Product #: 844

HMIS® ratings Health: 1*

Flammability: 3 Physical hazard: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our

knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified

in the text.

MSDS sections updated Transport Information: Agency Name and Packaging Type/Transport Mode Selection

trade_name Water Base Stainless Steel Maintainer

Product #: 844 Revision date: 22-JUL-2008 Print date: 22-JUL-2008 5