

# Marking Paint (solvent-based) - Aerosol



# Material Safety Data Sheet

TO: MSDS USERS

Please find below the material safety data sheet as per your request.

The information presented in these forms is believed to be correct and sufficient to meet the requirements of OSHA Hazard Communication standard (29 CFR 1910.1200) concerning worker's right to know. In order for the information contained in the MSDS to be most helpful we recommend that these forms be made available to all those who handle or may otherwise be exposed to the product.

The following material safety data sheet covers the hazardous ingredients associated with more than one color aerosol product. As per 29 CFR 1900.1200 paragraph (g); whenever the hazards associated with similar mixtures are the same, then one MSDS may be prepared to cover several products.

This MSDS covers the following AerVOE-Pacific aerosol products.

## MARKING PAINT

REGULAR		FLUORESCENT	16 oz. I. A. C.		HIGH DELIVERY
201 RED	207 WHITE	220 RED	261S RED	270S FLUORESCENT RED	281 RED
202 YELLOW	208 HI VISIBILITY YELLOW	222 ORANGE	262S YELLOW	272S FLUORESCENT ORANGE	282 YELLOW
203 BLUE	209 LIGHT BLUE	224 GREEN	263S BLUE	274S FLUORESCENT GREEN	288 FLUORESCENT ORANGE
204 GREEN	210 SILVER	226 YELLOW	264S GREEN	275S FLUORESCENT RED/ORANGE	
205 ORANGE	212 PURPLE	227 BLUE	265S ORANGE	279S FLUORESCENT PINK	
206 BLACK	213 BROWN	229 PINK	266S BLACK		
		230 RED/ORANGE	267S WHITE		

PRODUCT NAME: MARKING PAINT - ALL COLORS

PRODUCT CODE: 17A

HMIS CODES: H F R P  
2 4 1 X

## SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: AerVOE-Pacific Company, Inc.

ADDRESS: 1198 Mark Circle, Gardnerville, NV 89410

INFORMATION PHONE: 775-782-0100

EMERGENCY PHONE: 1-800-424-9300

DATE REVISED: 12-04-01

REASON REVISED: Updated

## SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION OCCUPATIONAL EXPOSURE LIMITS

HAZARDOUS COMPONENTS	WEIGHT PERCENT	OSHA PEL	ACGIH TLV	OTHER	LD50 SPECIES & ROUTE	LC50 SPECIES & ROUTE
*XYLENE (CAS 1330 20 7)	20	100 PPM	100 PPM		4300 mg / kg RAT (ORAL)	6700 PPM; 4 hr RAT (INHA)
MINERAL SPIRITS (CAS 8052 41 3)	<5.0%	100 PPM	100 PPM		N/A	N/A
ACETONE (CAS 67 64 1)	<5.0%	750 PPM	750 PPM		9750 mg / kg RAT (ORAL)	6700 PPM / 4 hr RAT (INHA)
*GLYCOL ETHER EB ACETATE (CAS 112 07 2)	1	N/A	N/A	N/A	N/A	N/A
*HEXANE (CAS 110 54 3)	12	50 PPM	50 PPM		28,710 mg / kg RAT (ORAL)	N/A
PROPANE (CAS 74 98 6)	10	1000 PPM	1000 PPM		N/A	N/A
ISOBUTANE (CAS 75 28 5)	<5.0%	800 PPM	800 PPM	ESTIMATED	N/A	57 PPH /15 min RAT (INHA)
NORMAL BUTANE (CAS 106 97 8)	5	600 PPM	600 PPM		N/A	658 mg / L; 4 hr RAT (INHA)

\*Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

NOTE: N/A applies to not available or not applicable

PRODUCT CODE: 17A

## SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT: 10° F / -12° C

SPECIFIC GRAVITY (H2O=1): 0.9

ODOR THRESHOLD: N/A

VAPOR DENSITY: Heavier than air

EVAPORATION RATE: Faster than n-Butyl Acetate

APPEARANCE AND ODOR: Opaque Liquid / Solvent Based Odor

Coefficient of Water/Oil Dist: N/A  
SOLUBILITY IN WATER: Negligible  
FREEZING POINT: N/A  
pH: N/A

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: -26° F / -32° C

METHOD USED: Estimated  
FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: 0.8% UPPER: 9.6%

EXTINGUISHING MEDIA: Foam, Alcohol Foam, CO<sub>2</sub>, Dry Chemical, Water Fog

SPECIAL FIRE FIGHTING PROCEDURES: Water spray may be ineffective, but water spray may be used to cool containers exposed to heat or fire to prevent pressure build up. Self-contained breathing apparatus should be used if product is involved in fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may explode due to pressure build up from extreme heat or fire. Aerosol spray is extremely flammable.

FLAMMABILITY: Yes - Flammable aerosol under conditions of sparks, flame, or hot surfaces.

SENSITIVITY TO IMPACT: Do not puncture

SENSITIVITY TO STATIC DISCHARGE: Primarily vapors

## SECTION V - REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: High temperatures

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon Monoxide and Carbon Dioxide

HAZARDOUS POLYMERIZATION: Will not occur

## SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: May cause dizziness or nausea.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: SKIN - May cause irritation or burning sensation.

EYES - Primary irritation.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: May cause irritation or burning sensation.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: N/A

HEALTH HAZARDS (ACUTE AND CHRONIC): INHALATION - Anesthetic. Irritation of the respiratory tract, or nervous system depression (characterized by headache, dizziness, nausea or possible unconsciousness). SKIN OR EYE CONTACT - Primary irritation. Prolonged or repeated contact to skin may cause dermatitis - exercise due care. (Canada Only: Xylene meets Canadian WHMIS hazard classification criteria for developmental toxicity [fetotoxicity]. In studies in which animals were exposed to xylene via inhalation, adverse effects on the developing fetus were observed).

CARCINOGENICITY: None known

NTP? No

IARC MONOGRAPHS? No

OSHA REGULATED? No

TERATOGENICITY: N/A

MUTAGENICITY: N/A

TOXICOLOGICALLY SYNERGISTIC PRODUCT: N/A

MEDICAL CONDITION GENERALLY AGGRAVATED BY EXPOSURE: None known

EMERGENCY AND FIRST AID PROCEDURES: VAPORS - Remove from exposure and restore breathing, seek medical attention.

SPLASH - (SKIN) Wash affected area, remove contaminated clothing, see physician if any irritation persists.

SPLASH - (EYES) Flush immediately with water for 15 minutes and take to a physician.

## SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition - Flames, sparks, static electricity & electrical. Ventilate area, avoid run off into sewer by diking, and soak up with inert absorbent using non-sparking type tools.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 120° F / 49° C. Do not store or use near heat, sparks or flame.

OTHER PRECAUTIONS: Do not get in eyes. Do not breathe vapors. Avoid skin contact. Do not take internally. Smoking while using this product must be strictly prohibited. In addition to all other hazards and precautions - dust from sanding the dry paint films should be treated as a nuisance dust with a TLV of 10mg/cubic meter.

## SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: Outdoors - Recommend an approved mechanical particulate filter to remove any airborne overspray. In restricted areas with poor ventilation, use a NIOSH approved Organic Cartridge Respirator. For concentrations above the exposure limit, use a positive air supplied respirator.

VENTILATION: All application areas should be adequately ventilated in order to keep the items in SECTION II below their exposure limits.

PROTECTIVE GLOVES: Impervious gloves (natural rubber) are recommended to prevent skin contact.

EYE PROTECTION: Safety glasses with side shields are recommended to prevent eye contact.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Impervious apron (natural rubber) is recommended to prevent skin contact. Eye wash fountain and safety shower.

WORK / HYGIENIC PRACTICES: Avoid prolonged or repeated contact. Do not breathe vapors. Wash contaminated clothing prior to reuse.

## SECTION IX - DISCLAIMER

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.

**Marking Paint, non-Fluorescent (solvent-based) - Bulk**

# Material Safety Data Sheet

TO: MSDS USERS

Please find below the material safety data sheet as per your request.

The information presented in these forms is believed to be correct and sufficient to meet the requirements of OSHA Hazard Communication standard (29 CFR 1910.1200) concerning worker's right to know. In order for the information contained in the MSDS to be most helpful we recommend that these forms be made available to all those who handle or may otherwise be exposed to the product.

The following material safety data sheet covers the hazardous ingredients associated with more than one color bulk product. As per 29 CFR 1900.1200 paragraph (g); whenever the hazards associated with similar mixtures are the same, then one MSDS may be prepared to cover several products.

This MSDS covers the following AerVOE-Pacific bulk products.

**MARKING PAINT - REGULAR COLORS**

201 RED	204 GREEN	207 WHITE	210 SILVER
202 YELLOW	205 ORANGE	208 HI VISIBILITY YELLOW	212 PURPLE
203 BLUE	206 BLACK	209 LIGHT BLUE	213 BROWN

**PRODUCT NAME:** MARKING PAINT - ALL REGULAR COLORS    **PRODUCT CODE:** 17B    **HMIS CODES:** H 2 F 3 R 0 P X

**SECTION I - MANUFACTURER IDENTIFICATION**

**MANUFACTURER'S NAME:** AerVOE-Pacific Company, Inc.    **ADDRESS:** 1198 Mark Circle, Gardnerville, NV 89410  
**INFORMATION PHONE:** 775-782-0100    **EMERGENCY PHONE:** 1-800-424-9300  
**DATE REVISED:** 03-14-02    **REASON REVISED:** Updated

**SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION OCCUPATIONAL EXPOSURE LIMITS**

HAZARDOUS COMPONENTS	WEIGHT PERCENT	OSHA PEL			LD50 SPECIES & ROUTE	LC50 SPECIES & ROUTE
		OSHA PEL	ACGIH TLV	OTHER		
*XYLENE (CAS 1330 20 7)	44	100 PPM	100 PPM		4300 mg / kg RAT (ORAL)	6700 PPM; 4 hr RAT (INHA)
*ETHYL BENZENE (CAS 100 41 4)	5	100 PPM	100 PPM	N/A	3500 mg / kg RAT (ORAL)	N/A
MINERAL SPIRITS (CAS 8052 41 3)	5	100 PPM	100 PPM		N/A	N/A
*GLYCOL ETHER EB ACETATE (CAS 112 07 2)	2	N/A	N/A	N/A	N/A	N/A
<b>210 SILVER ALSO INCLUDES THE FOLLOWING:</b>						
ACETONE (CAS 67 64 1)	< 5 %	750 PPM	750 PPM		9750 mg / kg RAT (ORAL)	6700 PPM / 4 hr RAT (INHA)

\*Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

**NOTE:** N/A applies to not available or not applicable

PRODUCT CODE: 17B

**SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS**

**BOILING POINT:** 149° to 289°F (65° to 142.8° C)    **SPECIFIC GRAVITY (H20=1):** 1.1    **COEFFICIENT OF WATER/OIL DIST:** N/A  
**ODOR THRESHOLD:** N/A    **VAPOR DENSITY:** Heavier than air    **SOLUBILITY IN WATER:** Negligible  
**EVAPORATION RATE:** Slower than n-Butyl Acetate    **APPEARANCE AND**    **ODOR:** Opaque Liquid / Solvent Based Odor  
**COATING V.O.C. :** 6.24 lbs / Imp gal    5.20 lbs / US gal    523 gms / ltr    **FREEZING POINT:** N/A    **pH:** N/A

**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**

**FLASH POINT:** 59° to 74°F (15° to 23.3° C)    **METHOD USED:** Estimated  
**FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER:** 0.7%    **UPPER:** 7.0%  
**EXTINGUISHING MEDIA:** Foam, Alcohol Foam, CO2, Dry Chemical, Water Fog  
**SPECIAL FIRE FIGHTING PROCEDURES:** Water spray may be ineffective, but water spray may be used to cool containers exposed to heat or fire to prevent pressure build up. Self-contained breathing apparatus should be used if product is involved in fire.  
**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Closed containers may rupture due to pressure build up from extreme heat or fire.  
**FLAMMABILITY:** Yes - Flammable liquid under conditions of sparks, flame, or hot surfaces.  
**SENSITIVITY TO IMPACT:** Do not puncture    **SENSITIVITY TO STATIC DISCHARGE:** Primarily vapors

**SECTION V - REACTIVITY DATA**

**STABILITY:** Stable    **CONDITIONS TO AVOID:** High temperatures  
**INCOMPATIBILITY (MATERIALS TO AVOID):** Strong oxidizing agents  
**HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:** Carbon Monoxide and Carbon Dioxide  
**HAZARDOUS POLYMERIZATION:** Will not occur

**SECTION VI - HEALTH HAZARD DATA**

**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** May cause dizziness or nausea.  
**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** SKIN - May cause irritation or burning sensation.  
EYES - Primary irritation.  
**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** May cause irritation or burning sensation.  
**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** N/A  
**HEALTH HAZARDS (ACUTE AND CHRONIC):** INHALATION - Anesthetic. Irritation of the respiratory tract, or nervous system depression (characterized by headache, dizziness, nausea or possible unconsciousness). SKIN OR EYE CONTACT - Primary irritation. Prolonged or repeated contact to skin may cause dermatitis - exercise due care.  
**CARCINOGENICITY:** None known    **NTP?** No    **IARC MONOGRAPHS?** No    **OSHA REGULATED?** No  
**TERATOGENICITY:** N/A    **MUTAGENICITY:** N/A    **TOXICOLOGICALLY SYNERGISTIC PRODUCT:** N/A  
**MEDICAL CONDITION GENERALLY AGGRAVATED BY EXPOSURE:** None known  
**EMERGENCY AND FIRST AID PROCEDURES:** VAPORS - Remove from exposure and restore breathing, seek medical attention.  
**SPLASH - (SKIN)** Wash affected area, remove contaminated clothing, see physician if any irritation persists.  
**SPLASH - (EYES)** Flush immediately with water for 15 minutes and take to a physician.

**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Remove all sources of ignition - Flames, sparks, static electricity & electrical. Ventilate area, avoid run off into sewer by diking, and soak up with inert absorbent using non-sparking type tools.  
**WASTE DISPOSAL METHOD:** Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers.  
**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** Do not store above 120° F / 49° C. Do not store or use near heat, sparks or flame.  
**OTHER PRECAUTIONS:** Do not get in eyes. Do not breathe vapors. Avoid skin contact. Do not take internally. Smoking while using this product must be strictly prohibited. In addition to all other hazards and precautions - dust from sanding the dry paint films should be treated as a nuisance dust with a **TLV of 10mg/cubic meter.**

**SECTION VIII - CONTROL MEASURES**

**RESPIRATORY PROTECTION:** Outdoors - Recommend an approved mechanical particulate filter to remove any airborne overspray. In restricted areas with poor ventilation, use a NIOSH approved Organic Cartridge Respirator. For concentrations above the exposure limit, use a positive air supplied respirator.  
**VENTILATION:** All application areas should be adequately ventilated in order to keep the items in SECTION II below their exposure limits.  
**PROTECTIVE GLOVES:** Impervious gloves (natural rubber) are recommended to prevent skin contact.  
**EYE PROTECTION:** Safety glasses with side shields are recommended to prevent eye contact.  
**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** Impervious apron (natural rubber) is recommended to prevent skin contact. Eye wash fountain and safety shower.  
**WORK / HYGIENIC PRACTICES:** Avoid prolonged or repeated contact. Do not breathe vapors. Wash contaminated clothing prior to reuse.

**SECTION IX - DISCLAIMER**

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.

**Marking Paint, Fluorescent (solvent-based) - Bulk**

# Material Safety Data Sheet

TO: MSDS USERS

Please find below the material safety data sheet as per your request.

The information presented in these forms is believed to be correct and sufficient to meet the requirements of OSHA Hazard Communication standard (29 CFR 1910.1200) concerning worker's right to know. In order for the information contained in the MSDS to be most helpful we recommend that these forms be made available to all those who handle or may otherwise be exposed to the product.

The following material safety data sheet covers the hazardous ingredients associated with more than one color bulk product. As per 29 CFR 1900.1200 paragraph (g); whenever the hazards associated with similar mixtures are the same, then one MSDS may be prepared to cover several products.

This MSDS covers the following AerVOE-Pacific bulk products.

**MARKING PAINT - FLUORESCENT COLORS**

220 RED	224 GREEN	229 PINK
222 ORANGE	226 YELLOW	230 RED/ORANGE
	227 BLUE	

**PRODUCT NAME:** MARKING PAINT - ALL FLUORESCENT COLORS **PRODUCT CODE:** 17B2 **HMIS CODES:** H 2 F 3 R 0 P X

**SECTION I - MANUFACTURER IDENTIFICATION**

**MANUFACTURER'S NAME:** AerVOE-Pacific Company, Inc.  
**INFORMATION PHONE:** 775-782-0100  
**DATE REVISED:** 03-14-02

**ADDRESS:** 1198 Mark Circle, Gardnerville, NV 89410  
**EMERGENCY PHONE:** 1-800-424-9300  
**REASON REVISED:** Updated

**SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION  
OCCUPATIONAL EXPOSURE LIMITS**

HAZARDOUS COMPONENTS	WEIGHT PERCENT	OSHA PEL			LD50 SPECIES & ROUTE	LC50 SPECIES & ROUTE
		OSHA PEL	ACGIH TLV	OTHER		
*XYLENE (CAS 1330 20 7)	23	100 PPM	100 PPM		4300 mg / kg RAT (ORAL)	6700 PPM; 4 hr RAT (INHA)
*ETHYL BENZENE (CAS 100 41 4)	4	100 PPM	100 PPM	N/A	3500 mg / kg RAT (ORAL)	N/A
PETROLEUM NAPHTHA  (CAS 64742-89-8)	16	400 PPM	400 PPM		> 7.10 g / kg RAT (ORAL) > 2.84 g / kg RAT (DERMAL)	15,000 PPM / 4 hr RAT (INHA)

\*Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

**NOTE:** N/A applies to not available or not applicable**PRODUCT CODE:** 17B2**SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS**

**BOILING POINT:** 222° to 278°F / 106° to 137° C **SPECIFIC GRAVITY (H2O=1):** 1.2 **COEFFICIENT OF WATER/OIL DIST:** N/A  
**ODOR THRESHOLD:** N/A **VAPOR DENSITY:** Heavier than air **SOLUBILITY IN WATER:** Negligible  
**EVAPORATION RATE:** Slower than n-Butyl Acetate **APPEARANCE AND ODOR:** Opaque Liquid / Solvent Based Odor  
**COATING V.O.C. :** 5.08 lbs / Imp gal 4.23 lbs / US gal 507 gms / ltr **FREEZING POINT:** N/A **pH:** N/A

**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**

**FLASH POINT:** 20° F / -7° C **METHOD USED:** Estimated **FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER:** 1.0% **UPPER:** 8.0%  
**EXTINGUISHING MEDIA:** Foam, Alcohol Foam, CO2, Dry Chemical, Water Fog  
**SPECIAL FIRE FIGHTING PROCEDURES:** Water spray may be ineffective, but water spray may be used to cool containers exposed to heat or fire to prevent pressure build up. Self-contained breathing apparatus should be used if product is involved in fire.  
**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Closed containers may rupture due to pressure build up from extreme heat or fire.  
**FLAMMABILITY:** Yes - Flammable liquid under conditions of sparks, flame, or hot surfaces.  
**SENSITIVITY TO IMPACT:** Do not puncture **SENSITIVITY TO STATIC DISCHARGE:** Primarily vapors

**SECTION V - REACTIVITY DATA**

**STABILITY:** Stable **CONDITIONS TO AVOID:** High temperatures  
**INCOMPATIBILITY (MATERIALS TO AVOID):** Strong oxidizing agents  
**HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:** Carbon Monoxide and Carbon Dioxide  
**HAZARDOUS POLYMERIZATION:** Will not occur

**SECTION VI - HEALTH HAZARD DATA**

**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** May cause dizziness or nausea.  
**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** SKIN - May cause irritation or burning sensation.  
 EYES - Primary irritation.  
**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** May cause irritation or burning sensation.  
**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** N/A  
**HEALTH HAZARDS (ACUTE AND CHRONIC):** INHALATION - Anesthetic. Irritation of the respiratory tract, or nervous system depression (characterized by headache, dizziness, nausea or possible unconsciousness). SKIN OR EYE CONTACT - Primary irritation. Prolonged or repeated contact to skin may cause dermatitis - exercise due care.  
**CARCINOGENICITY:** None known **NTP?** No **IARC MONOGRAPHS?** No **OSHA REGULATED?** No  
**TERATOGENICITY:** N/A **MUTAGENICITY:** N/A **TOXICOLOGICALLY SYNERGISTIC PRODUCT:** N/A  
**MEDICAL CONDITION GENERALLY AGGRAVATED BY EXPOSURE:** None known  
**EMERGENCY AND FIRST AID PROCEDURES:** VAPORS - Remove from exposure and restore breathing, seek medical attention.  
 SPLASH - (SKIN) Wash affected area, remove contaminated clothing, see physician if any irritation persists.  
 SPLASH - (EYES) Flush immediately with water for 15 minutes and take to a physician.

**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Remove all sources of ignition - Flames, sparks, static electricity & electrical. Ventilate area, avoid run off into sewer by diking, and soak up with inert absorbent using non-sparking type tools.  
**WASTE DISPOSAL METHOD:** Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers.  
**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** Do not store above 120° F / 49° C. Do not store or use near heat, sparks or flame.  
**OTHER PRECAUTIONS:** Do not get in eyes. Do not breathe vapors. Avoid skin contact. Do not take internally. Smoking while using this product must be strictly prohibited. In addition to all other hazards and precautions - dust from sanding the dry paint films should be treated as a nuisance dust with a **TLV of 10mg/cubic meter.**

**SECTION VIII - CONTROL MEASURES**

**RESPIRATORY PROTECTION:** Outdoors - Recommend an approved mechanical particulate filter to remove any airborne overspray. In restricted areas with poor ventilation, use a NIOSH approved Organic Cartridge Respirator. For concentrations above the exposure limit, use a positive air supplied respirator.  
**VENTILATION:** All application areas should be adequately ventilated in order to keep the items in SECTION II below their exposure limits.  
**PROTECTIVE GLOVES:** Impervious gloves (natural rubber) are recommended to prevent skin contact.  
**EYE PROTECTION:** Safety glasses with side shields are recommended to prevent eye contact.  
**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** Impervious apron (natural rubber) is recommended to prevent skin contact. Eye wash fountain and safety shower.  
**WORK / HYGIENIC PRACTICES:** Avoid prolonged or repeated contact. Do not breathe vapors. Wash contaminated clothing prior to reuse.

**SECTION IX - DISCLAIMER**

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.