



Material Safety Data Sheet

Creation Date 22-Jan-2009

Revision Date 23-Sep-2009

Revision Number 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name 2-Methyl-1-propanol

Cat No. AC398950000; AC398950010; AC398951000

Synonyms Isobutanol; Isobutyl alcohol

Recommended Use Laboratory chemicals

Company
Fisher Scientific
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Entity / Business Name
Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number
For information in the US, call: 800-ACROS-01
For information in Europe, call: +32 14 57 52 11

Emergency Number, Europe: +32 14 57 52 99
Emergency Number, US: 201-796-7100

CHEMTREC Phone Number, US: 800-424-9300
CHEMTREC Phone Number, Europe: 703-527-3887

2. HAZARDS IDENTIFICATION

DANGER!

Emergency Overview

Flammable liquid and vapor. Risk of serious damage to eyes. Irritating to respiratory system and skin. Vapors may cause drowsiness and dizziness.

Appearance Colorless

Physical State Liquid

odor aromatic

Target Organs Skin, Respiratory system, Eyes, Central nervous system (CNS), Liver

Potential Health Effects

Acute Effects

Principle Routes of Exposure

Eyes	Risk of serious damage to eyes. Causes severe eye irritation and possible burns.
Skin	Irritating to skin. May be harmful in contact with skin.
Inhalation	Irritating to respiratory system. May be harmful if inhaled. May cause drowsiness and dizziness.
Ingestion	May be harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic Effects	May cause adverse liver effects. Tumorigenic effects have been reported in experimental animals..

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions Central nervous system disorders. Preexisting eye disorders. Skin disorders.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Haz/Non-haz

Component	CAS-No	Weight %
Isobutyl alcohol	78-83-1	99

4. FIRST AID MEASURES

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek immediate medical attention/advice.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Obtain medical attention.
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. Obtain medical attention.
Ingestion	Do not induce vomiting. Obtain medical attention.
Notes to Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flash Point	28°C / 82.4°F
Method	No information available.
Autoignition Temperature	430°C / 806°F
Explosion Limits	
Upper	10.9 vol %
Lower	1.6 vol %
Suitable Extinguishing Media	CO ₂ , dry chemical, dry sand, alcohol-resistant foam. Cool closed containers exposed to fire with water spray.
Unsuitable Extinguishing Media	Water may be ineffective.
Hazardous Combustion Products	No information available.
Sensitivity to mechanical impact	No information available.
Sensitivity to static discharge	No information available.

Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA**Health 2****Flammability 3****Instability 0****Physical hazards N/A****6. ACCIDENTAL RELEASE MEASURES****Personal Precautions**

Use personal protective equipment. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Should not be released into the environment.

Methods for Containment and Clean Up

Soak up with inert absorbent material. Keep in suitable and closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. HANDLING AND STORAGE**Handling**

Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use explosion-proof equipment. Take precautionary measures against static discharges.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat and sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Engineering Measures**

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment.

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
Isobutyl alcohol	TWA: 50 ppm	(Vacated) TWA: 150 mg/m ³ (Vacated) TWA: 50 ppm TWA: 300 mg/m ³ TWA: 100 ppm	IDLH: 1600 ppm TWA: 50 ppm TWA: 150 mg/m ³

Component	Quebec	Mexico OEL (TWA)	Ontario TWAEV
Isobutyl alcohol	TWA: 152 mg/m ³ TWA: 50 ppm	TWA: 150 mg/m ³ TWA: 50 ppm STEL: 75 ppm STEL: 225 mg/m ³	TWA: 150 mg/m ³ TWA: 50 ppm

NIOSH IDLH: Immediately Dangerous to Life or Health

Personal Protective Equipment**Eye/face Protection**

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid
Appearance	Colorless
odor	aromatic
Odor Threshold	No information available.
pH	No information available.
Vapor Pressure	11.7 mbar @ 20°C
Vapor Density	2.6 (Air = 1.0)
Viscosity	No information available.
Boiling Point/Range	108°C / 226.4°F
Melting Point/Range	-108°C / -162.4°F
Decomposition temperature	No information available.
Flash Point	28°C / 82.4°F
Evaporation Rate	(Butyl Acetate = 1.0)
Specific Gravity	0.800
Solubility	Partly soluble in water
log Pow	No data available
Molecular Weight	74.12
Molecular Formula	C4 H10 O

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Conditions to Avoid	Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	Strong oxidizing agents, Acid anhydrides, Acid chlorides
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO ₂)
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions .	None under normal processing..

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product Information See actual entry in RTECS for complete information.

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Isobutyl alcohol	2460 mg/kg (Rat)	2000 mg/kg (Rabbit)	6.5 mg/L (Rat) 4 h

Irritation Severe eye irritant. Irritating to respiratory system and skin.

Toxicologically Synergistic Products No information available.

Chronic Toxicity

Carcinogenicity There are no known carcinogenic chemicals in this product

Sensitization No information available.

Mutagenic Effects No information available.

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

Other Adverse Effects Tumorigenic effects have been reported in experimental animals.. See actual entry in RTECS for complete information.

Endocrine Disruptor Information No information available

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Do not empty into drains.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Isobutyl alcohol	EC50 48 h 230 mg/L	Not listed	EC50 = 1224.6 mg/L 15 min	EC50 48 h 1030 mg/L

Persistence and Degradability No information available

Bioaccumulation/ Accumulation No information available

Mobility .

Component	log Pow
Isobutyl alcohol	0.79

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Isobutyl alcohol - 78-83-1	U140	-

14. TRANSPORT INFORMATION

DOT

UN-No UN1212
Proper Shipping Name ISOBUTANOL
Hazard Class 3
Packing Group III

TDG

UN-No UN1212
Proper Shipping Name ISOBUTANOL
Hazard Class 3
Packing Group III

IATA

UN-No 1212
Proper Shipping Name ISOBUTANOL
Hazard Class 3
Packing Group III

IMDG/IMO

UN-No 1212
Proper Shipping Name ISOBUTANOL
Hazard Class 3
Packing Group III

15. REGULATORY INFORMATION

International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	CHINA	KECL
Isobutyl alcohol	X	X	-	201-148-0	-		X	X	X	X	KE-24894 X

Legend:

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B)).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313

Not applicable

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

Not applicable

Clean Air Act

Not applicable

OSHA

Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Isobutyl alcohol	5000 lb	-

California Proposition 65

This product does not contain any Proposition 65 chemicals.

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Isobutyl alcohol	X	X	X	-	X

U.S. Department of Transportation

Reportable Quantity (RQ):	Y
DOT Marine Pollutant	N
DOT Severe Marine Pollutant	N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade

Serious risk, Grade 3

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

B2 Flammable liquid

D2B Toxic materials

**16. OTHER INFORMATION****Prepared By**

Regulatory Affairs
Acros Organics BVBA
Tel: 800-ACROS-01

Creation Date

22-Jan-2009

Print Date

23-Sep-2009

Revision Summary

"***", and red text indicates revision

Disclaimer

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of MSDS